Albany



JAPAN CERAMICS

26 Daisy Street
Revesby NSW 2212
P 02 9772 2088
E sales@japanceramics.com.au
japanceramics.com.au

ALBANY

COLOURS, FORMATS & FINISHES





MATT | P3

	White	Cream	Grey
600 x 600mm	●	●	●
450 x 450mm	●	●	●
300 x 600mm	●	●	●
300 x 300mm	●	●	●

TEXTURED | P5

600 x 600mm	●	●	●
450 x 450mm	●	●	●

FINISH: **MATT** CATEGORY: GLAZED FLOOR TILES | EDGE DETAIL: UNRECTIFIED | V RATING: V2
FINISH: **TEXTURED** CATEGORY: GLAZED FLOOR TILES | EDGE DETAIL: UNRECTIFIED | V RATING: V2







300 x 300mm
ALBWH30 (matt)



300 x 600mm
ALBWH36 (matt)




450 x 450mm
ALBWH45 (matt)
ALBWH45T (textured)



600 x 600mm
ALBWH60 (matt)
ALBWH60T (textured)





300 x 300mm
ALBCR30 (matt)



300 x 600mm
ALBCR36 (matt)



450 x 450mm
ALBCR45 (matt)
ALBCR45T (textured)



600 x 600mm
ALBCR60 (matt)
ALBCR60T (textured)

JAPAN CERAMICS





300 x 300mm
ALBGR30 (matt)



300 x 600mm
ALBGR36 (matt)



450 x 450mm
ALBGR45 (matt)
ALBGR45T (textured)



600 x 600mm
ALBGR60 (matt)
ALBGR60T (textured)



JAPAN CERAMICS

Technical Specifications

Properties	Test Method	Required Value	Value	Applies to
Water absorption	ISO 10545-3	⩽ 0.5%	⩽ 3%	All finishes
Determination of dimensions	ISO 10545-2	Length and width ± 0.5% Thickness ± 5.00% Edge straightness ± 0.5% Surface flatness ± 5%	Length and width 0.5% Thickness 5.0% Edge straightness 0.6% Surface flatness 0.5%	All finishes
Breaking strength	ISO 10545-4	⩾ 1300 N	2184 N	All finishes
Abrasion resistance	ISO 10545-6	Class 3 min.	Complies with standards	All finishes
Slip resistance (wet pendulum test)	Wet pendulum test	N/A	P3 – Matt P5 – Textured	Matt, Textured
Chemical resistance	ISO 10545-13	GB min.	Complies with standards	All finishes
Stain resistance	ISO 10545-14	Class 3 min.	Complies with standards	All finishes
Origin	N/A	N/A	Australia	All finishes
Shade variation	N/A	N/A	V2	Full range



JAPAN CERAMICS

Packing Information

Tile Description		Quantity per Box	Quantity per m2		Quantity per Pallet	
Size (mm)	Finish	Pieces	Pieces	Weight	m2	Boxes
300 x 300	Matt	22	11.11	14.05kg	95.04	48
300 x 600	Matt	8	5.56	20.00kg	69.12	48
450 x 450	Matt Textured	7	4.93	16.74kg	113.60	80
600 x 600	Matt Textured	4	2.78	19.97kg	69.12	48



The data and information contained in these specification sheets are indicative only unless stated otherwise. As Japan Ceramics cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation. The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.

JAPAN CERAMICS

IMPORTANT NOTE:

Slip ratings are indicative only. Actual performance may vary depending on installation, surface conditions, and maintenance.

Slip Test Report – Batch Certification

National Ceramic Industries Australia Pty Ltd, ABN: 83 100 467 267

175 Racecourse Rd, Rutherford NSW 2320, Australia, Tel: +61 2 4931 8400 Fax: +61 2 4931 8499, www.ncia.com.au

Slip Resistance Classification of New Pedestrian Surfaces Materials Australia Standard AS 4586:2013 Appendix A (Wet Pendulum Test Method)

Production Year	2025	**Test Sheet No:**	Batch Test	**Issue Date**	27/08/2025

Testing was conducted using a 96 rubber slider in accordance with the above Standard.
Slider was prepared/conducted using P400C paper and 3 µm lapping film

Code/s	Tile Name/s	Tile Size (cm)	Test Location	Cleaning Pre-testing	Results	Classification of Pedestrian Surfaces Materials according to the above Standard
ZAY1045A	Albany White	45X45	Tile Surface	Water & Scrubbing	Recorded	P3
ZAY2045A	Albany Grey	45X45	Tile Surface	Water & Scrubbing	Recorded	
ZAY3045A	Albany Cream	45X45	Tile Surface	Water & Scrubbing	Recorded	
ZAY1055A	Albany White	30X60	Tile Surface	Water & Scrubbing	Recorded	
ZAY2055A	Albany Grey	30X60	Tile Surface	Water & Scrubbing	Recorded	
ZAY3055A	Albany Cream	30X60	Tile Surface	Water & Scrubbing	Recorded	
ZAY1060A	Albany White	60X60	Tile Surface	Water & Scrubbing	Recorded	
ZAY2060A	Albany Grey	60X60	Tile Surface	Water & Scrubbing	Recorded	
ZAY3060A	Albany Cream	60X60	Tile Surface	Water & Scrubbing	Recorded	
Temperature (indoor)	20.8°C					
Testing Instrument	Pendulum Friction Tester, Calibration Date: 24 June 2024		National Ceramic Industries Australia Pty Ltd			
Reporting Officer	Hong Lu		NCIA Tiles Testing Laboratory			

IMPORTANT NOTE:
Slip ratings are indicative only. Actual performance may vary depending on installation, surface conditions, and maintenance.

ALBANY RANGE


White, Cream&Grey

NCIA Standard Slip Resistant Finish

BPN P5 slip resistance

300x600

Slip Resistant Finish P5 (Standard)



WET PENDULUM TEST

SLIP RESISTANCE REPORT **AS 4586-2013**

CLASSIFICATION OFPEDESTRIANSURFACE MATERIALS ACCORDING TO
AS 4586 - 2013 WETPENDULUM TEST

Class	Slider 96 (4S)	Slider 55
P5	>54	>44
P4	45-54	40-44
P3	35-44	35-39
P2	25-34	20-34
P1	12 - 24	<20
P0	<12	

ncia
AUSTRALIA'S TILE MANUFACTURER

175 Racecourse Rd, Rutherford NSW 2320
PO Box 765 Maitland NSW 2320
Australia
Tel: +61 2 4931 8400 Fax: +61 2 4931 8499

IMPORTANT NOTE:
Slip ratings are indicative only. Actual performance may vary depending on installation, surface conditions, and maintenance.

ALBANY RANGE


White, Cream&Grey

NCIA Standard Slip Resistant Finish

BPN P5 slip resistance

450x450

Slip Resistant Finish P5 (Standard)



WET PENDULUM TEST

SLIP RESISTANCE REPORT	AS 4586-2013

CLASSIFICATION OFPEDESTRIANSURFACE MATERIALS ACCORDING
TO
AS 4586 - 2013 WETPENDULUM TEST

Class	Slider 96 (4S)	Slider 55
P5	>54	>44
P4	45-54	40-44
P3	35-44	35-39
P2	25-34	20-34
P1	12 - 24	<20
P0	<12	

ncia
AUSTRALIA'S TILE MANUFACTURER

175 Racecourse Rd, Rutherford NSW 2320
PO Box 765 Maitland NSW 2320
Australia
Tel: +61 2 4931 8400 Fax: +61 2 4931 8499

IMPORTANT NOTE:
Slip ratings are indicative only. Actual performance may vary depending on installation, surface conditions, and maintenance.

ALBANY RANGE


White, Cream&Grey

NCIA Standard Slip Resistant Finish

BPN P5 slip resistance

600x600

Slip Resistant Finish P5 (Standard)



WET PENDULUM TEST

SLIP RESISTANCE REPORT	AS 4586-2013

CLASSIFICATION OFPEDESTRIANSURFACE MATERIALS ACCORDING
TO
AS 4586 - 2013 WETPENDULUM TEST

Class	Slider 96 (4S)	Slider 55
P5	>54	>44
P4	45-54	40-44
P3	35-44	35-39
P2	25-34	20-34
P1	12 - 24	<20
P0	<12	

ncia
AUSTRALIA'S TILE MANUFACTURER

175 Racecourse Rd, Rutherford NSW 2320
PO Box 765 Maitland NSW 2320
Australia
Tel: +61 2 4931 8400 Fax: +61 2 4931 8499