Lusso



JAPAN CERAMICS

26 Daisy Street
Revesby NSW 2212
P 02 9772 2088
E sales@japanceramics.com.au
japanceramics.com.au

LUSSO

JAPAN CERAMICS
26 Daisy Street
Revesby NSW 2212
P 02 9772 2088
E sales@japanceramics.com.au
japanceramics.com.au

COLOURS, FORMATS & FINISHES



Honed	White	Naturale	Terra	Grigio	Nero
600 x 1200mm	●	●		●	
600 x 600mm	●	●	●	●	●
300 x 600mm	●	●	●	●	●
300 x 300mm	●	●	●	●	●
73 x 298mm	●	●	●	●	●

In/Out | P4					
600 x 600mm	●	●	●	●	●

FINISH: **HONED** | CATEGORY: PORCELAIN TILES | EDGE DETAIL: RECTIFIED | V RATING: V3
FINISH: **IN/OUT** | CATEGORY: PORCELAIN TILES | EDGE DETAIL: RECTIFIED | V RATING: V3



Colour variation is an inherent property of all kiln-fired products. Tiles supplied may vary from samples provided. All slip ratings are provided subject to the guidelines outlined in our terms and conditions.

© JAPAN CERAMICS



600 x 600mm
LUSWH60H (honed)
LUSWH60M (in/out)

600 x 1200mm
LUSWH612H (honed)

73 x 298mm
LUSWH753H (honed)

300 x 300mm
LUSWH30H (honed)

300 x 600mm
LUSWH36H (honed)



600 x 600mm
LUSNAT60H (honed)
LUSNAT60M (in/out)

600 x 1200mm
LUSNAT612H (honed)

73 x 298mm
LUSNAT753H (honed)

300 x 300mm
LUSNAT30H (honed)

300 x 600mm
LUSNAT36H (honed)

JAPAN CERAMICS



73 x 298mm
LUSTER753H (honed)

300 x 300mm
LUSTER30H (honed)

300 x 600mm
LUSTER36H (honed)

600 x 600mm
LUSTER60H (honed)
LUSTER60M (in/out)



600 x 600mm
LUSGY60H (honed)
LUSGY60M (in/out)

600 x 1200mm
LUSGY612H (honed)

73 x 298mm
LUSGY753H (honed)

300 x 300mm
LUSGY30H (honed)


300 x 600mm
LUSGY36H (honed)

JAPAN CERAMICS






73 x 298mm
LUSNER753H (honed)



300 x 300mm
LUSNER30H (honed)



300 x 600mm
LUSNER36H (honed)



600 x 600mm
LUSNER60H (honed)
LUSNER60M (in/out)



JAPAN CERAMICS

Technical Specifications

Properties	Test Method	Required Value	Value	Applies to
Water absorption	ASTM C373	⩽ 0.5%	⩽ 0.11%	Full range
Breaking strength	ASTM C648	⩾ 1100 N	⩾ 2143 N	Full range
Abrasion resistance	ASTM C1027	As reported	Class 3	Full range
Slip resistance (wet pendulum test)	AS 4586:2013	N/A	P4 – In/Out P5 - Textured	In/Out, Textured
Slip resistance (oil wet ramp test)	AS 4586:2013	N/A	N/A	Full range
Chemical resistance	ASTM C650	As reported	Class A	Full range
Stain resistance	ASTM C1378	As reported	Class A	Full range
Origin	N/A	N/A	China	Full range
Shade variation	N/A	N/A	V3	Full range



JAPAN CERAMICS

Packing Information

Tile Description		Quantity per Box	Quantity per m2		Quantity per Pallet	
Size (mm)	Finish	Pieces	Pieces	Weight	m2	Boxes
73 x 298	Honed	40	44.44	18.00kg	40.50	45
300 x 300	Honed	11	11.11	22.22kg	55.44	56
300 x 600	Honed	8	5.56	22.22kg	57.60	40
600 x 600	Honed In/Out	4	2.78	22.22kg	57.60	40
600 x 1200	Honed	2	1.39	25.69kg	40.32	28



The data and information contained in these specification sheets are indicative only unless stated otherwise. As Japan Ceramics cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation. The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.

JAPAN CERAMICS

IMPORTANT NOTE:
Slip ratings are indicative only. Actual performance may vary depending on installation, surface conditions, and maintenance.

Slip Check to AS 4586-2013

Lusso IN/OUT

Report Number: R22211
Report Date: 22 October 2020
Total Number of Pages 2

Accredited for compliance with ISO/IEC 17025 – Testing

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration and inspection reports

This test report shall not be reproduced unless in full, without written approval of Safe EnvironmentsPtyLtd

Issued by

Safe Environments Pty Ltd
Unit 4, 40 Bessemer Street
Blacktown NSW 2148

Prepared for

Japan Ceramics
26 Daisy Street
Revesby NSW 2212

Approved by

Dale Rowell
AuthorisedSignatory

SlipCheck
CREATING SAFE ENVIRONMENTS
www.FloorSlipTest.com.au

Unit 4/40 Bessemer St
Blacktown NSW 2148
Phone 02 9621 3706
info@SafeEnvironments.com.au

22 October 2020

Test Report No. R22211

Slip Resistance ClassificationofNewPedestrianSurface Materials

AS 4586-2013 Appendix A (Wet Pendulum Test)

The slip resistance classification has been determined for unused surfaces using specific conditions. Factors such as usage, cleaning systems, applied coatings and patterns of wear may affect the characteristics of the surface after classification. Standards Australia Handbook 198:2014 *Guide to the specification and testing of slip resistance of pedestrian surfaces* provides guidance for the selection of slip resistant pedestrian surfaces classified in accordance with AS 4586-2013. It is recommended that this test report be read in conjunction with AS 4586 and HB 198.

Requested by:	Japan Ceramics
Client Address:	26 Daisy Street Revesby NSW 2212
Product Manufacturer:	Max Glory
Product Description:	Lusso IN/OUT
Test conducted according to:	AS 4586:2013 Appendix A
Location:	4/40 Bessemer Street, Blacktown NSW 2148
Conducted by:	Oshi Barkat
Date:	22 October 2020
Sample:	Unfixed
Rubber slider used:	Slider 96
Slope of specimen:	Tested on a flat level surface
Direction of Test:	NA
Temperature:	21 C
Cleaning:	None
Conditioned:	Grade P 400 paper dry followed by wet lapping film

	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5
Mean BPN of last 3 swings:	61	64	64	60	62

Reported SRV of Sample:	**62**
Class:	**P5**

This test report shall not be reproduced unless in full, without written approval of Safe EnvironmentsPtyLtd